Code: C16 M-403

6448

BOARD DIPLOMA EXAMINATION MARCH/APRIL - 2019 DIPLOMA IN MECHANICAL ENGINEERING THERMAL ENGINEERING II FOURTH SEMESTER EXAMINATION

Time: 3 Hours Total Marks: 80

PART - A $(3m \times 10 = 30m)$

Note 1:Answer all questions and each question carries 3 marks

2:Answers should be brief and straight to the point and shall not exceed 5 simple sentences

- 1. Write expression for external work of evaporation for a. wet steam b. dry steam at a given pressure
- 2. State any three features of supercritical boilers
- 3. Show that the enthalpy drop is equal to the change of internal energy in hyperbolic process
- 4. Draw T-s and h-s diagrams for Throttling process
- 5. Define the term steam nozzle. List any two types of steam nozzles
- 6. Define compounding. Name any two types of compounding
- 7. Define a) bleeding of steam turbines b) reheating of steam turbine
- 8. Write the classification of gas turbines
- 9. State the principle of Ram effect
- 10. State the function of differential

PART - B $(10m \times 5 = 50m)$

Note 1:Answer any five questions and each carries 10 marks

- 2:The answers should be comprehensive and the criteria for valuation is the content but not the length of the answer
- 11. a. Define critical point. What are the pressure and temperature of steam at critical point? (4 MARKS)
 - b. Draw T-h diagram in respect of steam and show the salient points on it. (6 MARKS)
- 12. Explain the working of Lamont boiler with a neat sketch

www.manaresults.co.in

Page: 1 of 2

Code: C16 M-403

- 13. Steam is throttled from a pressure of 11.5 bar to 1.4 bar. If the steam is dry saturated at the end of the expansion, Find
 - a. Dryness fraction of steam at beginning
 - b. Change in entropy
- 14. Dry saturated steam at a pressure of 15 bar expands isentropically in an nozzle and is discharged at a pressure of 1 bar. Find the dryness fraction of steam at the exit of nozzle and also find the final velocity of steam neglecting the initial velocity using steam tables.
- 15. The angles at inlet and discharge of the blading of a reaction turbine are 35° and 20° respectively at the mean blade ring diameter. The speed of rotation is 25 rev/s and at a particular moving ring the mean blade ring diameter is 0.6 m and the steam conditions 1.4 bar, 0.96 dry. Estimate
 - a. The required height of the blade to pass 3.26 kg/s of steam
 - b. Power developed by the ring
- 16. Draw Atkinson's cycle for constant volume gas turbines and explain the sequence of operations
- 17. Explain the working principle of rocket engine with a neat sketch
- 18. Draw the layout of an automobile transmission system and write the function of each component

- xxx -