

## C14-EE-605

## 4745

# BOARD DIPLOMA EXAMINATION, (C-14) OCT/NOV-2017

### DEEE—SIXTH SEMESTER EXAMINATION

#### MICRO CONTROLLERS AND APPLICATIONS

Time: 3 hours [ Total Marks: 80

#### PART—A

 $3 \times 10 = 30$ 

**Instructions**: (1) Answer **all** questions.

- (2) Each question carries three marks.
- (3) Answers should be brief and straight to the point and shall not exceed *five* simple sentences.
- 1. Differentiate between microprocessor and microcontroller.
- 2. List the features of Intel 8085 microprocessor.
- **3.** Differentiate between Harvard and Von Neumann architecture.
- **4.** List the interrupts in 8051 on the basis of priority.
- **5.** What is the function of TCON register?
- **6.** List the features of 8051 microcontroller.
- **7.** Define fetch cycle, execution cycle.
- **8.** Define opcode and operand with respect to instruction.
- 9. List various symbols used in drawing flowcharts.
- **10.** Write simple program to perform single byte addition

/4745 1 [Contd...
www.ManaResults.co.in

4

6

**Instructions**: (1) Answer any **five** questions.

- (2) Each question carries ten marks.
- (3) Answers should be comprehensive and the criterion for valuation is the content but not the length of the answer.
- **11.** (a) Explain the concept of peripheral interfacing.
  - (b) Draw the functional block diagram of 8085 microprocessor. 6
- **12.** Draw the functional block diagram of a 8051 microcontroller and explain the function of each block. 5+5=10
- **13.** Explain the addressing modes of 8051 with examples.
- **14.** Explain the following instructions:
  - (a) MOV A, @R<sub>i</sub>
  - (b) ADDA, #data
  - (c) CLR A
  - (d) SWAP A
  - (e) XRL A, R<sub>n</sub>
- **15.** (a) Write a program to perform subtraction of two 8-bit numbers stored in location 8500 H and 8501 H store the result in the location 8502 H.
  - (b) Write a program to generate 5 ms time delay by operating timer () mode 1. Assume the 8051 XTAL frequency is 12 MHz.
- **16.** (a) Explain how information is exchanged between program counter and the stack.
  - (b) Define subroutine and explain its use.
- **17.** Explain the working of 8051 microcontroller as dot matrix display interface with a neat sketch.
- **18.** Explain the working of 8051 microcontroller in stepper motor control with a neat sketch. 5+5=10

\* \* \*

/4745 2 AA7(A)—PDF www.ManaResults.co.in