

## 4745

## BOARD DIPLOMA EXAMINATION, (C-14) OCT/NOV-2018 DEEE - SIXTH SEMESTER EXAMINATION

## MICRO CONTROLLERS & APPLICATIONS

*Time* : 3 hours [ Total Marks: 80

## PART—A

 $3 \times 10 = 30$ 

- **Instructions:** (1) Answer **all** questions.
  - (2) Each question carries **three** marks.
  - (3) Answers should be brief and straight to the point and shall not exceed five simple sentences.
  - 1. Define the terms: Bit, Nibble, Byte.
  - 2. Distinguish between micro, mini and large computers.
  - **3.** Compare Embedded and External memory devices.
  - **4.** Draw the pin diagram of 8051 microcontroller.
  - **5.** State the need of timers and counters in 8051 microcontroller.
  - **6.** List the features of 8051 microcontroller.
  - **7.** State the need for an instruction set.
  - **8.** List the five addressing modes of 8051
  - **9.** Draw the flowchart to multiply two 8-bit numbers.
  - 10. Write an example for single byte, two byte and three byte instructions.

/4745 1 [Contd... **PART-B**  $10 \times 5 = 50$ 

**Instructions:** (1) Answer any **five** questions.

- (2) Each questions carries ten marks.
- (3) Answers should be comprehensive and the criteria for valuation are the content but not the length of the answer.
- **11.** a) Draw the functional block diagram of 8255 and explain the function of each block.
  - b) Draw the Interface diagram of 8255 with 8085 processor.
- **12.** Draw the block diagram of a microcontroller and explain the funtion of each block.
- **13.** List the addressing modes of 8051 and explain them with examples.
- **14.** a) Explain the fetch cycle, execution cycle and instruction cycle.
  - b) Define the terms: machine language, assembly language.
- **15.** a) Write a program to convert a given HEX number to BCD number.
  - b) Write a program to find the sum of given N numbers.
- **16.** Explain the sequence of program when subroutine is called and executed
- **17.** Explain the working of 8051 microcontroller in dot matrix display interface.
- **18.** Explain the working of 8051 microcontroller as keyboard interface.

\* \* \*

**/4745** 2 [AA8