## Code No: 126VF

### JAWAHARLAL NEHRU TECHNOLOGICAL UNIVERSITY HYDERABAD B. Tech III Year II Semester Examinations, May - 2019 HEAT TRANSFER (Common to ME, AME, MSNT)

#### Time: 3 hours

**Note:** This question paper contains two parts A and B.

Part A is compulsory which carries 25 marks. Answer all questions in Part A. Part B consists of 5 Units. Answer any one full question from each unit. Each question carries 10 marks and may have a, b, c as sub questions.

### PART - A

#### What is the convection mode of heat transfer? 1.a) [2] What are the applications of heat transfer? b) [3] What is the function of fin? [2] c) What is critical radius of insulation? d) [3] Differentiate the free and forced convection. e) [2] What are the advantages of dimensional analysis? f) [3] What is film wise condensation? g) [2] What is the concept of shape factor? h) [3] What is the difference between regenerator and recuperator? i) [2] What are the advantages of NTU method over the LMTD method? **i**) [3]

### PART - B

#### (50 Marks)

**R15** 

Max. Marks: 75

(25 Marks)

- 2.a) A Stainless steel plate is of 2 cm thick is maintained at a temperature of  $550^{\circ}$ C at one face and  $50^{\circ}$ C on the other. The thermal conductivity of stainless steel at  $300^{\circ}$ C is 19.1 W/m K. Calculate the heat transferred through the material per unit area.
  - b) In what way is the science of heat transfer different from thermodynamics? Explain. [5+5]

#### OR

- 3. Derive the general conduction equation for
  a) Cylindrical co-ordinate
  b) Spherical co-ordinates, the system being with uniform heat generation and unsteady state. [5+5]
- 4.a) Explain why the conductivity of metals decreases and conductivity of insulating material increases with increases in temperature.
  - b) A metallic plate, 3cm thick is maintained at  $400^{\circ}$ C on one side and  $100^{\circ}$ C on the other side. How much heat is transferred through the plate? Take k for the metallic plate as k=370 W/m-K. [5+5]

#### OR

- 5.a) What is critical thickness of insulation on a small diameter wire or pipe, explain its physical significance and derive an expression for the same.
  - b) Calculate the rate of heat loss for a red brick wall of length 5m, height 4m, and thickness 0.25m, the temperature of the inner surface is  $110^{\circ}$ C and that of the outer surface is  $40^{\circ}$ C. The thermal conductivity of red brick k = 0.70 W/m-K. Calculate also the temperature of the inner surface from the inner wall. [5+5]

- 6.a) Differentiate between mechanisms of heat transfer by free and forced convection. Mention some of the areas where these mechanisms are predominant.
  - b) Water at  $75^{\circ}$ C flows through a 0.005 m diameter tube with a velocity of 1m/s. If the tube wall temperature is  $25^{\circ}$ C, make calculations for the heat transfer coefficient. Use the correlation, St = 0.023 Re 0.2 Pr 0.667. The thermo-physical properties of water are: Thermal conductivity is 0.647 W/(m.K); Viscosity is 1.977 kg/h.m; Density is 1000 kg/m3; Specific heat 4.187 kJ/(kg.K). [5+5]

OR

- 7.a) Describe Buckingham's method of  $\pi$ -terms to formulate a dimensionally homogenous equation.
  - b) A flat plate 1m wide and 1.5 m long is to be maintained at  $90^{\circ}$ C in air when free stream temperature is  $10^{\circ}$ C. Determine the velocity at which air must flow over the plate so that the rate of energy dissipation from the plate is 3.75kW. [5+5]
- 8.a) Draw the boiling curve for pool boiling of water and explain flow regimes.
- b) Saturated steam at a temperature of  $65^{\circ}$ C condenses on a vertical surface at  $55^{\circ}$ C. Determine the thickness of the condensate film at locations 0.2 m and 1.0 m from the top. Also calculate condensate flow rate at these locations. [5+5]

#### OR

- 9.a) Derive an expression for the shape factor in case of a radiation exchange between two surfaces.
- b) Show that the emissive power if a black body is  $\pi$  times the intensity of emitted radiation. [5+5]
- 10.a) Derive an expression for LMTD in case of a counter flow heat exchanger.
  - b) A cross-flow heat exchanger with both fluids unmixed is used to heat water (Cp= 4.18 kJ/kgK) from  $50^{\circ}$ C to  $90^{\circ}$ C, flowing at the rate of 1.0 kg/s. Determine the overall heat transfer coefficient if the hot engine oil (Cp= 1.9 kJ/kgK) flowing at the rate of 3 kg/s enters at  $100^{\circ}$ C. The heat transfer area is  $20 \text{ m}^2$ . [5+5]

#### OR

11. A chemical having specific heat of 3.3 kJ/kg k flowing at the rate of 20000 kg/hr enters a parallel flow heat exchanger at  $120^{\circ}$ C. The flow rate of cooling water is 50000 kg/hr with an inlet temperature of  $20^{\circ}$ C. The heat transfer area is  $10 \text{ m}^2$  and the overall heat transfer coefficient is 1050 W/m<sup>2</sup>K. Find

a) The effectiveness of the heat exchanger

b) The outlet temperature of water and chemical.

Take for water, specific heat=4.186KJ/kg K.

[5+5]

---00000----

# www.manaresults.co.in