IV B.Tech I Semester Supplementary Examinations, October/November - 2017 DESIGN AND DRAWING OF IRRIGATION STRUCTURES (Civil Engineering)

Time: 3 hours Max. Marks: 75

Note: Answer any ONE of the following Two Questions Assume any of the data if required Khosla curves are allowed

Design a sluice (tank sluice with tower head) taking off from a tank with a following data:

: 0.40m /sec Discharge Top width of the bund : 2.0 m Side slopes : 2H: 1V Top level of the bund : +61.00Ground level at the site : +55.50 Sill of the sluice at off-take : +55.00Maximum water level in the tank : +59.00Full tank level : +58.00Average low water level : +56.00Good hard soil for foundation is available at +54.50.

Details of canal below the sluice

Bed level : +55.00 F.S.L : +55.50 Bed width : 1.50 m

Side slopes : 1.5H : 1V with top of bank at +56.50

Draw the longitudinal section. Assume any other suitable data.

Design a surplus weir of a tank forming a chain of tanks. The combined catchment area of the group of tank is 40 square kilometers and the area of the catchment intercepted by the upper tank is 30 square kilometers.

It is decided to store water in the tank to the level of $+\ 112.00m$ limiting the submersion of foreshore lands up to a level of $+\ 112.75m$. The ground level at the proposed site of work is $+\ 111.00m$, and the ground level below the proposed surplus slopes of till it reaches $+\ 110.00m$ in about 6metres distance. The tank bund has a top width of 2meters at level $+\ 114.50$ with 2:1 side slopes on either side. The tank bunds are designed for a saturation gradient of 4:1 with one meter clear cover. The foundations are of hard gravel at a level of $+\ 109.50m$ near the site of work. Assume any other suitable data. Draw the Plan, Longitudinal Section and Longitudinal Elevation of the weir.